



Meets ADA requirements
Specially designed for
Barrier Free Application
Conforms with ANSI A156.2
Series 4000, Grade 2
Exceeds 400,000 cycles



Optional tactile warning
meets handicap and fire code


Push in and
turn button function

Coil compression
springs provide great
strength and durability

UL LISTED 3 HOUR RATED
1/2" Throw deadlatch completely
reversible for flat & beveled doors


PIONEER

SL SERIES (NON CLUTCH MECHANISM) CSL SERIES (CLUTCH MECHANISM) OPTIONAL THRU BOLT INSTALLATION




Solid brass 6 pin "C" keyway
cylinder. Available with
Interchangeable Core


Individual spring on each
side to prevent lever sag,
maintain reliability and reduce
maintenance



AG DESIGN



RL DESIGN



SPECIFICATIONS

APPLICATIONS

For offices, schools, hospitals, apartments, hotel/motel, residential, commercial and public buildings.

DOOR RANGES

1 3/8" to 1 3/4" thickness doors.

BACKSET

2 3/4" Standard, 2 3/8", 3 3/4" and 5" optional.

LATCHBOLT

1/2" Throw solid brass, reversible for RH or LH applications. UL Listed.

LATCH FACEPLATE

2 1/4" x 1 1/8", adjustable for flat or beveled doors 1/8" in 2", for 2 3/4" backset.

Optional 2 1/4" x 1" for 2 3/8" backset.

ANSI STANDARDS

Meets or exceeds requirements of BHMA/ANSI A156.2 Series 4000, Grade 2 (FF-H 106C), 400,000 cycles.

EXPOSED TRIM

Wrought brass, bronze or stainless steel, levers are Zinc casting, plated to match trim finish.

KEYING

6-pin "C" keyway cylinder, 2 keys per lock. Keying as per individual job requirement.

CYLINDER & KEYWAYS

6 pin solid brass "C" keyway standard. Schlage E, Schlage C-K, Russwin D1-2-3-4, Corbin 59/60, Corbin-Russwin L4, Sargent LA-LB-LC, Falcon/Weiser E, Arrow A, Yale 8, Yale GA and Kwikset. Can also accept Medeco, Assa, Kaba and Cal-Royal (HSK) High Security Cylinders.

CLUTCH

Clutch available on all keyed locks and privacy functions. Prefix "C" before part number.

INTERCHANGEABLE CORE

Interchangeable Core locks will accept compatible 6 or 7 pin cores with BEST, FALCON and ARROW. Prefix "IC" before part number. Available combined or uncombined. Temporary construction cores available. Factory keying with control key and master key available.

STRIKES

ASA strike standard, "T" and full lip stike available on request.

TACTILE & LEAD LINING available upon request.


PIONEER SL SERIES FINISHES AND FUNCTIONS

FINISHES AVAILABLE

BHMA SYMBOL	US CODE	DESCRIPTION
605	US3	Polished Brass
606	US4	Satin Brass
609	US5	Antique Brass
612	US10	Satin Bronze
613	US10B	Oil Rubbed Bronze
619	US15	Satin Nickel
625	US26	Polished Chrome
626	US26D	Satin Chrome

Refer to price list for stock finishes and functions

DOOR PREPARATION




Lifetime
Warranty

BHMA
CERTIFIED
Be Safe. Be Secure. Look for the Mark.

UL
US
3 HOUR FIRE RATED
UL10C, UBC7-2-1997


SL00
ICSL00
CSL00
ANSI: F109



ENTRANCE/OFFICE LOCK

Turn/Push button locking. Pushing and turning button locks outside lever requiring use of key until button is manually unlocked. Pushing button locks outside lever until unlocked with key or inside lever is turned.

SL10
CSL10
ANSI: F77



PATIO

Deadlocking latch bolt operated by lever from either side. Outside lever is locked by push button inside and unlocked by rotating inside lever or closing door.


SL01
ICSL01
CSL01
ANSI: F82



ENTRANCE LOCK PUSH BUTTON

Pushing button in inside lever locks outside lever. Turning inside lever or operating key in outside lever releases button automatically. Closing door does not release button. Button cannot be fixed in lock position. Inside lever always free. Latch bolt automatically deadlocks when door is closed.

SL20
CSL20
ANSI: F76



PRIVACY LOCK

Latch bolt operated by lever from either side. Outside lever is locked by push button inside and unlocked by emergency release outside. Turning inside lever or closing door releases push button.


SL03
ICSL03
CSL03
ANSI: F84



CLASSROOM LOCK

Dead locking latch bolt operated by lever from either side except when outside lever is locked from outside by key. When outside lever is locked, latch bolt is operated by turning inside lever.

SL30
ANSI: F75



PASSAGE SET

Latch bolt operated by lever from either side at all times.

SL05
ICSL05
CSL05
ANSI: F86



STOREROOM LOCK

Dead locking latch bolt operated by key in outside lever or by rotating inside lever. Outside lever is always fixed.

SL40



DUMMY LEVER

Single dummy trim for one side of door. Pull only.


SL80
ICSL80
CSL80
ANSI: F89



EXIT LOCK CONNECTING ROOM WITH KEY

Deadlocking latch bolt operated with key from inside only. Blank plate outside.


SL50
ANSI: F89



EXIT LOCK

Blank plate outside. Inside lever always unlocked.

SL101
ICSL101
CSL101
ANSI: F90



DORMITORY/ASSISTED LIVING

Deadlocking latch bolt operated by lever from either side except when outside lever is locked by key or by push button on inside lever. Key in outside lever locks or unlocks outside lever. Outside key releases push button when locked from inside. Rotating inside lever or closing the door releases push button.

HOW TO ORDER:
For "AG" or "RL" designs, replace design name.
Example: SL00 entrance in "AG" is AG00.

⚙️ "IC" Indicates function available with BEST, FALCON & ARROW Interchangeable Core.

⚙️ "CSL" Indicates function available with clutch

OTHER FUNCTIONS NOT LISTED AVAILABLE UPON REQUEST