

ACCENTRA

ASSA ABLOY

Experience a safer  
and more open world

# 1500 SERIES

## Traditional Exit Device



ACCENTRA

ASSA ABLOY

ASSA ABLOY is transitioning the Yale Commercial brand to ACCENTRA. This affects only the brand name; the products and product numbers will remain unchanged. Prior to May 20, 2024, products may be shipped either as Yale Commercial brand or ACCENTRA brand. Products shipping after May 20, 2024, will be branded ACCENTRA.

## TABLE OF CONTENTS

### Contents

Introduction .....	3
Benefits & Features.....	4
Finishes .....	5
How to Order .....	6
1500(F) Rim.....	7
1510(F) Surface Vertical Rod.....	8
1520(F) Concealed Vertical Rod .....	9
1530(F) Mortise .....	10
Trim Designs .....	11-12
Exit Device Trims.....	13-14
Applications Chart.....	15
Applications.....	16-17
Cylinders.....	18-20
Strikes .....	21
Accessories .....	22
Mullions.....	23-24
Technical Specifications & Listings.....	25

### 1500 Traditional Exit Devices

1500 Series Traditional Exit Devices are the perfect solution for modern retrofit applications that require maintaining the look and integrity of historic architectural motifs. Available with a variety of trims and options, the 1500 Series is able to suit a range of decor and application requirements.

## INTRODUCTION

ASSA ABLOY ACCENTRA™ offers innovative and reliable products to solve the challenges of commercial, retail, hospitality, assisted living, mixed-use, and multi-family properties. Our door hardware expertise extends beyond products to people - and provides the service and support you expect.

Featuring durable products to meet all your facilities' requirements - and the quality you expect from a leader in the hardware industry.

ACCENTRA Exit Devices			
7000 Series	6000 Series	2100 Series	1800 Series
 <p><b>7000 Series</b> BHMA CERTIFIED</p> <ul style="list-style-type: none"> <li>Ideal for facilities that require durability and innovation to meet their security needs</li> <li>Wide &amp; Narrow Stile Applications</li> <li>Rim, SquareBolt, Mortise, SVR &amp; CVR</li> <li>Mechanical &amp; Electro-Mechanical Functions</li> <li>Available with Motorized Electric Latch Retraction</li> <li>Constructed with high quality steel and heavy-duty components</li> <li>16 Standard finishes including BSP (Black Suede Powder Coat)</li> <li>ANSI/BHMA Certified Grade 1</li> <li>UL Rated for Panic &amp; Fire, Windstorm Rated Options (refer to local codes)</li> <li>5 Year Warranty and Two-Year Limited Warranty on Electronic Components</li> </ul>	 <p><b>6000 Series</b> BHMA CERTIFIED</p> <ul style="list-style-type: none"> <li>Ideal for facilities that require modern form and full functionality to meet their life safety needs</li> <li>Wide &amp; Narrow Stile Applications</li> <li>Rim, Squarebolt, CVR, SVR &amp; Mortise</li> <li>Mechanical &amp; Electro-Mechanical Functions</li> <li>Available with Motorized Electric Latch Retraction</li> <li>Aluminum rail assembly with Architectural Metals</li> <li>Solid Cast Flush End Cap</li> <li>ANSI/BHMA Certified Grade 1</li> <li>UL Rated for Panic &amp; Fire</li> <li>10 Year Warranty and Two-Year Limited Warranty on Electronic Components</li> </ul>	 <p><b>2100 Series</b> BHMA CERTIFIED</p> <ul style="list-style-type: none"> <li>Ideal for commercial applications and budget conscious end users</li> <li>Narrow &amp; Wide Stile Applications</li> <li>Rim, Squarebolt, CVR &amp; SVR</li> <li>Mechanical Functions</li> <li>ANSI/BHMA Grade 1 Certified</li> <li>UL Rated for Panic &amp; Fire</li> <li>Architectural &amp; Painted Finishes</li> <li>3 Year Warranty</li> </ul>	 <p><b>1800 Series</b> BHMA CERTIFIED</p> <ul style="list-style-type: none"> <li>Ideal for back of the house where function and code compliance are the requirement</li> <li>Wide Stile Applications</li> <li>Rim &amp; SVR</li> <li>Mechanical Functions</li> <li>ANSI/BHMA Certified Grade 1</li> <li>UL Rated for Panic &amp; Fire</li> <li>Powder-coat Painted Finishes</li> <li>3 Year Warranty</li> </ul>

## BENEFITS & FEATURES

### Benefits

- **Great for retrofit applications:** Classic design allows for upgrade in historic buildings, on single or pairs of doors
- **Strong & reliable:** ANSI/BHMA Grade 1 certified for long life and durability

### Features

- Available in rim, mortise, surface vertical rod and concealed vertical rod
- Lever, handle and pull trim designs available for design continuity throughout a building
- 2-point hex-key dogging for standard devices enables quiet push-pull door operation during peak traffic hours
- Standard outside trim available with a choice of 6 and 7-pin, interchangeable core, patented and security rim cylinders, keyed as needed



## FINISHES

ANSI/BHMA Code Finish Description			
605 Bright Brass, Clear Coated	606 Satin Brass, Clear Coated	611 Bright Bronze, Clear Coated	612 Satin Bronze, Clear Coated
			
613E Dark Oxidized Satin Bronze - equivalent	619* Satin Nickel Plated, Clear Coated	626* Satin Chrome Plated	629 Bright Stainless Steel
			
630* Satin Stainless Steel	693 Black Painted	695 Dark Bronze Painted	BSP Black Suede Powder Coat
			
WSP White Suede Powder Coat			
			

\*Finish available with MicroShield® antimicrobial coating, additional finishes by special application. Consult factory for availability.

MicroShield coating may vary finish color from architectural standards. MicroShield is not intended as a substitute for traditional infection control programs such as hand hygiene or use of disinfectants. Coated products must still be cleaned to ensure the surfaces will be free of destructive microbes. ASSA ABLOY ACCENTRA™ makes no representations or warranties, express or implied, as to the efficacy of MicroShield.

## HOW TO ORDER

The following selection guide indicates the correct cylinder for each locking segment.

Quantity	X	0	Suffix	Size	Design	Trim	Finish	Other Info
15	<b>Third Position:</b> 0 - Rim Device 1 - SVR Device 2 - CVR Device 3 - Mortise Device		Suffix - Mechanical Feature: "F" - Fire Exit Device "L5" - Mortise Device, Entry by Key with/without Rigid Lever. Mortise Device EO or entry by key. "L8" - Mortise Device, Entry by Lever. "T5" - Mortise Device with Thumbpiece Trim "T8" - Mortise Device, Active Thumbpiece Trim.	<b>Size:</b> (DOW = Door Opening Width) "36" - Thru 36" (90cm) "48" - Thru 48" (120cm)	<b>Trim Design:</b> (Lever only.)	<b>Trim Model Number</b>	<b>Finish Code:</b> See Page 5	<b>Other Information:</b> <b>Door Hand</b> - All devices and lever handle trim. <b>Door Thickness</b> - over 1-3/4" (45mm). <b>Fastener Options</b> - Torx® Security Screws, SNB (wood, composite, or unreinforced metal doors). <b>Specialty Cylinders &amp; Components</b>

## Packaging

It is recommended that exit devices and trim for the same opening be ordered together. Standard product are for 1-3/4" (44mm) reinforced metal doors. Accessories detached from the device and trim should be specified separately. Materials by others are required to be fit for the purpose as detailed in this catalog and the product installation literature.

## 1500(F) RIM

The 1500(F) is a traditional exit device for single swing doors or pairs of doors with mullions of metal, wood or composite construction.



### Certification/Compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware  
 GXHX/GXHX7 - Fire exit hardware (F)  
 (4' x 8' single, 8' x 8' pairs, 3 hr.)  
 ANSI/BHMA Certified: A156.3 Type 1, Grade 1 

### Features

- Designed for wide stile doors
- Handed, specify hand (field reversible)

### Applications

- Single swing doors
- Pairs of doors with removable mullions
- Metal, wood or composite door materials

### Specifications

<b>Door Opening Width</b>	-36 for 30" - 36" (76cm - 91cm) doors -48 for 36" - 48" (91cm - 122cm) doors
<b>Door Thickness</b>	1-3/4" (44mm) standard
<b>Minimum Stile Width</b>	4-1/2" (114mm)
<b>Projection</b>	5-5/8" (143mm) active, 4-1/2" (114mm) depressed.
<b>Latchbolt</b>	3/4" (19mm) deadlocking stainless steel pullman-type
<b>Strike</b>	799 (panic & fire), 793 optional (double door application)
<b>Fasteners</b>	Machine screws and wood door fasteners standard for panic hardware. Sex nuts and bolts supplied standard for fire exit hardware.
<b>Trims</b>	620F series escutcheon trim, 630F series pull/thumbpiece trim. See pages 13-14.
<b>Dogging</b>	Hex key dogging supplied standard on panic devices
<b>Options</b>	Sex nuts and bolts
<b>Warranty</b>	1-year limited

## 1510(F) SURFACE VERTICAL ROD

The 1510(F) is a traditional surface vertical rod exit device for any door where two-point latching is desired (inactive doors of pairs in particular).

Packed for 7'0" high (2.13m) openings with recommended template. Field cut rods or use rod extensions for other applications.

### Certification/Compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware  
GXHX/GHX7 - Fire exit hardware (F)  
(8' x 8' pairs, 3 hr.)

ANSI/BHMA  
Certified: A156.3 Type 2, Grade 1 



### Features

- Designed for wide stile doors
- Handed, specify hand (field reversible)
- Positive action linkage on a deadlocking top pullman bolt
- Simultaneous direct pull bottom deadbolt
- When unlatched, device keeps both bolts retracted until door is shut

### Applications

- Pairs of doors
- Double egress
- Metal, wood or composite door materials

### Specifications

<b>Door Opening Width</b>	-36 for 30" - 36" (76cm - 91cm) doors -48 for 36" - 48" (91cm - 122cm) doors
<b>Door Opening Height</b>	Standard door height 7' (213cm), with the device centerline at 39-5/16" (100cm) from floor. Optional heights up to 8' (fire) and 10' (panic) available by using rod extensions.
<b>Door Thickness</b>	1-3/4" (44mm) standard
<b>Minimum Stile Width</b>	4-1/2" (114mm)
<b>Projection</b>	5-5/8" (143mm) active, 4-1/2" (114mm) depressed.
<b>Latchbolt</b>	Top: 3/4" (19mm) throw, pullman-type with automatic deadlatching Bottom: 5/8" (16mm) throw deadbolt, held retracted during door swing
<b>Vertical Rods</b>	1/2" (13mm) O.D. tubular brass, bronze or stainless steel with rod guides
<b>Strike</b>	Top: Roller type 791. Bottom: Flush mounted 790. 794 floor strike optional (threshold openings), 702 floor strike optional (BPL devices).
<b>Fasteners</b>	Machine screws and wood door fasteners standard for panic hardware. Sex nuts and bolts supplied standard for fire exit hardware.
<b>Trims</b>	620F series escutcheon trim, 630F series pull/thumbpiece trim. See pages 13-14.
<b>Dogging</b>	Hex key dogging supplied standard on panic devices
<b>Options</b>	Sex nuts and bolts, bottom pullman latch (panic only), rod extensions
<b>Warranty</b>	1-year limited

## 1520(F) CONCEALED VERTICAL ROD

The 1520(F) is a traditional concealed vertical rod exit device for metal doors where two-point latching is desired (inactive doors of pairs in particular.)

### Certification/Compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware  
GXHX/GXHX7 - Fire exit hardware (F)  
(8' x 8' pairs, 3 hr.)

ANSI/BHMA  
Certified: A156.3 Grade 1, Type 8, Grade 1 



### Features

- Designed for wide stile doors
- Handed, specify hand (field reversible)
- Positive action linkage on a deadlocking top pullman bolt
- Simultaneous direct pull bottom deadbolt
- When unlatched, device keeps both bolts retracted until door is shut

### Applications

- Pairs of doors
- Double egress
- Metal doors only

### Specifications

<b>Door Opening Width</b>	-36 for 30" - 36" (76cm - 91cm) doors -48 for 36" - 48" (91cm - 122cm) doors
<b>Door Opening Height</b>	Standard door height adjustable to 8' (244cm). Optional heights up to 10' (panic) available by using rod extensions.
<b>Door Thickness</b>	1-3/4" (44mm) standard
<b>Minimum Stile Width</b>	4-1/2" (114mm)
<b>Projection</b>	5-5/8" (143mm) active, 4-1/2" (114mm) depressed.
<b>Latchbolt</b>	Top: 3/4" (19mm) throw, pullman-type with automatic deadlatching Bottom: 5/8" (16mm) throw deadbolt, held retracted during door swing
<b>Vertical Rods</b>	1/2" (13mm) O.D. telescoping tubular rods
<b>Strike</b>	Top: Roller type 791. Bottom: Flush mounted 790. 794 floor strike optional (threshold openings)
<b>Fasteners</b>	Machine screws and wood door fasteners standard for panic hardware. Sex nuts and bolts supplied standard for fire exit hardware.
<b>Trims</b>	620F series escutcheon trim, 630F series pull/thumbpiece trim. See pages 13-14.
<b>Dogging</b>	Hex key dogging supplied standard on panic devices
<b>Options</b>	Sex nuts and bolts, rod extensions
<b>Warranty</b>	1-year limited

## 1530(F) MORTISE

The 1530(F) is a traditional exit device integrated with ACCENTRA 8700 series mortise lock for the active leaf of pairs and single doors where both exit device and security are required. Can be installed on metal, wood or composite doors. The 8700 series mortise lock used is modified for use with exit devices only.

### Certification/Compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware  
 GXHX/GXHX7 - Fire exit hardware (F)  
 (4' x 8' single, 8' x 8' pairs, 3 hr.)  
 (4' x 9' single, 8' x 9' pairs, 1-1/2 hr.)

ANSI/BHMA  
 Certified: A156.3 Type 3, Grade 1 



### Features

- Designed for wide stile and flush doors
- Handed; specify hand
- Two-piece mechanical 3/4" throw deadlocking stainless steel latchbolt

### Applications

- Single swing doors
- Pairs of doors with vertical rod devices or automatic flush bolts
- Metal, wood or compatible door materials

Order as follows, according to function.	
<b>1530-K5(F)</b>	(01) Exit only. (02) Entry by pull when dogged. (03) Key retracts latchbolt.
<b>1530-L5(F)</b>	(02) Entry by rigid lever when dogged. (03) Key retracts latchbolt.
<b>1530-T5(F)</b>	(02) Entry by pull when dogged. (03) Key retracts latchbolt.
<b>1530-L8(F)</b>	(08) Entry by lever lock/unlocked by key or lever only (passage).
<b>1530-T8(F)</b>	(05) Entry by thumbpiece lock/unlocked by key or thumbpiece only (passage).

### Specifications

<b>Door Opening Width</b>	-36 for 30" - 36" (76cm - 91cm) doors -48 for 36" - 48" (91cm - 122cm) doors
<b>Door Thickness</b>	1-3/4" (44mm) standard. 2" and 2-1/4" (51mm and 57mm) optional; specify when ordering.
<b>Minimum Stile Width</b>	4-1/2" (114mm)
<b>Projection</b>	5-5/8" (143mm) active, 4-1/2" (114mm) depressed.
<b>Latchbolt</b>	Two piece mechanical 3/4" (19mm) deadlocking stainless steel with anti-friction insert and auxiliary deadlocking latch
<b>Strike</b>	798 curved lip, non-handed standard. 712 optional for door pairs with astragals. 718 optional open back strike.
<b>Fasteners</b>	Machine screws and wood door fasteners standard for panic hardware. Sex nuts and bolts supplied standard for fire exit hardware.
<b>Trims</b>	350F/620F/650F series escutcheon trim, 630F/660F/670F series pull/thumbpiece trim. See pages 13-14.
<b>Dogging</b>	Hex key dogging supplied standard on panic devices
<b>Options</b>	Sex nuts and bolts
<b>Warranty</b>	1-year limited

## TRIM DESIGNS

## Standard

<b>Arcadia AR</b>  Projection: 3-1/4" (82mm)	<b>Augusta AU</b>  Projection: 2-5/8" (61mm)	<b>Carmel CR</b>  Projection: 3-1/8" (79mm)
<b>Jefferson JN</b>  Projection: 2-9/16" (65mm)	<b>Monroe MO</b>  Projection: 3" (76mm)	<b>Pacific Beach PB</b>  Projection: 3-5/16" (84mm)
<b>Pinehurst PN</b>  Projection: 3-1/16" (78mm)	<b>Virginia VI</b>  Projection: 3-1/8" (79mm)	<b>Hampton HA</b>  Projection: 3-3/8" (86mm)

Note: Projection dimensions are provided using the 620F series escutcheon plates.

## TRIM DESIGNS

Reflections® Levers 

<b>Hudson</b>	TB	UB	TC	TD	UC	
Projection	3-1/16" (78mm)	3-1/4" (83mm)	3" (76mm)	3-7/16" (87mm)	3-7/16" (87mm)	
<b>Spree</b>	RS	RT	RU	RV		
Projection	3-1/8" (79mm)	3-1/8" (79mm)	3-13/32" (87mm)	3" (76mm)		
<b>Seine</b>	TE	TG	TI	TJ	TK	
Projection	3" (76mm)	2-13/16" (61mm)	3-3/8" (85mm)	3-1/16" (78mm)	3-1/4" (83mm)	
<b>Thames</b>	TM	TN	TP	TR	TS	TQ
Projection	3-1/16" (78mm)	3-1/16" (78mm)	3-5/16" (84mm)	3-1/16" (78mm)	3-1/8" (80mm)	3-1/16" (78mm)
<b>Victoria</b>	TT	TU	TW	TX	UX	TY
Projection	2-11/16" (68mm)	3-1/4" (83mm)	3" (76mm)	3-5/8" (92mm)	3-7/16" (87mm)	3-5/16" (84mm)
<b>Niagara</b>	MA	RA	RB	RC		
Projection	2-13/16" (71mm)	3-11/16" (94mm)	2-13/16" (71mm)	2-13/16" (71mm)		

## Notes:

Projection dimensions are provided using the 620F Series escutcheon plates.

The following Reflections levers are not available in 629 or 630 finish: Victoria TT, TU, TW, TX, TY, UX; Seine TG, TJ, TK, TE, TI; Hudson TD. Please consider the 618 or 619 finish as an alternative. Reflections levers are not available with knurling option.


## EXIT DEVICE TRIMS

Rim and vertical rod devices use Universal Lifter Assembly #60-1500-0671-000, to connect to any 620 or 630 Series active trim. Mortise devices are supplied according to trim type and function desired. There is a 1530(F) Series device adequate for each 350, 650, 660 or 670 Series Trim charted.

### 350F, 620F and 650F Series Escutcheon Trim

- Certified ANSI/BHMA A156.3, Grade 1.
- Trim through-bolts to exit device for strength.
- Beveled sides improve attack resistance.
- Solid forged/cast escutcheon and free-wheeling trim for ideal protection.
- Flush cylinder in 6-pin applications for additional security.
- 1-3/4" (44mm) door standard. For doors through 2-1/4" (57mm) or shim-mounted devices, specify on order.
- Dimensions: 3" x 10-1/4" x 13/16" (76mm x 260mm x 19mm).
- Cylinders not included. See page 18-20 for cylinder options.

- Available with AR, AU, CR, JN, MO, PB, PN, VI, HA lever designs. See page 11.
  - Finishes: 605, 606, 611, 612, 613E, 619, 626, 629, 630, 693, BSP, WSP
- Available with Reflections® lever designs. See page 12.
  - Finishes: 605, 606, 611, 612, 613E, 619, 626, 629, 630, BSP, WSP
- Trim ordering example: AU626F x 626 x RHR.
- 5-year limited warranty.

       											
Application	Cylinder	Classroom/ Storeroom Cylinder Controls Thumbturn	Exit Only Blank Plate	Nightlatch Access by Key	Classroom Cylinder Controls Lever	Storeroom Cylinder Controls Lever	Nightlatch Cylinder by Lever	Passage	Dummy Trim Free- Wheeling	Dummy Rigid Lever	
1500(F) 1510(F) 1520(F)	Rim	603F*	620F	621F^	626F	626F*	627F^	628F	628F*	629F	
1530(F)	Mortise	--	620F	651F	356F	--	--	358F	--	358F	
ANSI		11/12	01	03	08	09	03	14	02	02	

\*09,12 and Free Wheeling 02 achieved with single trim modification at installation.

<sup>A</sup>Not recommended for use with vertical rod exit devices.

For 626, 629 & 630 finishes the escutcheon is plated to simulate stainless steel.

For 629 & 630 finishes the standard levers are plated to simulate stainless steel.

## EXIT DEVICE TRIMS

## 630F, 660F and 670F Series Pull/Thumbpiece Trim

- Certified ANSI/BHMA A156.3, Grade 1.
- Trim through-bolts to exit device for strength.
- Beveled sides improve attack resistance.
- Flush cylinder in 6-pin applications for additional security.
- 1-3/4" (44mm) door standard. For doors through 2-1/4" (57mm) or shim-mounted devices, specify on order.
- Plate Dimensions: 2-3/4" x 15-1/2" x 5/8" (70mm x 394mm x 16mm).
- Pull Dimensions: 6-7/16" (164mm) on centers x 2-1/8" (54mm) projection.
- Cylinders not included. See page 18-20 for cylinder options.
- Finishes: 605, 606, 612, 613E, 619, 626, 629, 630, 693, BSP, WSP
- Trim ordering example: 630F x 630
- 5-year limited warranty.

								
Applications	Cylinder	Exit Only Blank Plate	Nightlatch Access by Key	Nightlatch Cylinder by Pull	Classroom Cylinder Controls T-Piece	Storeroom Cylinder Controls T-Piece	Dummy Trim Pull Plate	Passage Active T-Piece
1500(F) 1510(F) 1520(F)	Rim	630F	631F <sup>A</sup>	632F <sup>A</sup>	633F	633F*	634F	635F
1530(F)	Mortise	630F	661F	662F	673F	--	634F	675F
ANSI		01	03	03	05	06	02	15

**\*06 achieved with single trim modification at installation.**

**<sup>A</sup>Not recommended for use with vertical rod exit devices.**

**For 626, 629 & 630 finishes the escutcheon is plated to simulate stainless steel.**

## APPLICATIONS CHART

Trim	Device (ANSI)	Rim (Type 1)	SVR (Type 2)	CVR (Type 8)	Mortise (Type 3)				
	Options	1500(F) See page 7	1510(F) See page 8	1520(F) See page 9	1530(F) See page 10				
ANSI	Function	Trim Options	Trim Options	Trim Options	Trim Options				
01	Exit Only (Blank Plate)		620F 630F		620F 630F		620F 630F		620F 630F
02	Pull to Open (Dummy Trim)		625F, 629F <sup>2</sup> 634F <sup>2</sup>		625F, 629F <sup>2</sup> 634F <sup>2</sup>		625F, 629F <sup>2</sup> 634F <sup>2</sup>		358F <sup>2</sup> , 634F <sup>2</sup> 654F
03	Entrance by Key & Pull (NL)		621F, 623F 627F <sup>2</sup> , 631F 632F <sup>2</sup>		621F, 623F 627F <sup>2</sup> , 631F 632F <sup>2</sup>		621F, 623F 627F <sup>2</sup> , 631F 632F <sup>2</sup>		356F <sup>2</sup> , 651F 661F, 662F <sup>2</sup>
05	Cylinder Controls Thumbpiece		633F		633F		633F		673F
—	Thumbpiece Always Active (Passage)		635F		635F		635F		675F
06	Key & Thumbpiece (Key Removable When Locked)		633F <sup>1</sup>		633F <sup>1</sup>		633F <sup>1</sup>		
08L	Cylinder Controls Lever		626F <sup>2</sup>		626F <sup>2</sup>		626F <sup>2</sup>		356F <sup>2</sup>
—	Lever Always Active (Passage)		628F <sup>2</sup>		628F <sup>2</sup>		628F <sup>2</sup>		358F <sup>2</sup>
09L	Key & Lever (Key Removable When Locked)		626F <sup>1,2</sup>		626F <sup>1,2</sup>		626F <sup>1,2</sup>		
11	Cylinder Controls Thumbtturn								
12	Key & Thumbtturn (Key Removable When Locked)		603F		603F		603F		

1 Field conversion required.

2 ADA compliant trim.

## APPLICATIONS

### Single Door




### Rim Exit Device - Standard Opening

- ANSI/BHMA A156.3 Type 1
- Easy installation
- Flush or wide stile metal, wood or composite doors
- Field reversible
- Exit only or with entry trim

<b>Exit Device</b>	Panic Exit: 1500 Fire Exit: 1500F
<b>Operating Trim</b>	620F or 630F Series
<b>Ordering Example</b>	1500-36" x AU626F x RHR x 626

### Double Egress Opening



### Two Surface Vertical Rod Exit Devices

- ANSI/BHMA A156.3, Type 2
- Two-point latch security
- Flush or wide stile metal, wood or composite doors
- Field reversible
- Smoke control or fire exit
- Two-way traffic control

<b>Exit Device</b>	Panic Exit: (2) 1510 Fire Exit: (2) 1510F
<b>Operating Trim</b>	620F or 630F Series
<b>Ordering Example</b>	2 each: 1510F-48" x LHR x 626

### Two Concealed Vertical Rod Exit Devices

- ANSI/BHMA A156.3, Type 8
- No exposed rods or latchbolts
- ADA compliant
- Flush or wide stile metal doors
- Field reversible
- Smoke control or fire exit
- Two-way traffic control

<b>Exit Device</b>	Panic Exit: (2) 1520 Fire Exit: (2) 1520F
<b>Operating Trim</b>	620F or 630F Series
<b>Ordering Example</b>	2 each: 1520F x 633F x LHR x 630

## APPLICATIONS

### Pair Of Doors With Center Mullion




### Two Rim Exit Devices - One Removable Mullion

- ANSI/BHMA A156.3
- Type 1
- Easy installation
- Flush or wide stile metal, wood or composite doors
- Exit only or with entry trim
- Recommended for easier traffic flow.

<b>Exit Device</b>	Panic Exit: (2) 1500 x M200 Fire Exit: (2) 1500F x M200F
<b>Operating Trim</b>	620F or 630F Series
<b>Ordering Example</b>	2 each: 1500-36" x AU626F x 1/2RHR x M200-70" x 626

### Pair Of Doors Without Mullion



### One Mortise - One Vertical Rod Exit Device

- The architectural choice for pairs of doors without mullions
- Flush or wide stile metal, wood or composite doors
- Panic or fire label openings

<b>Exit Device</b>	Panic Exit: 1530 Mortise x 1520 (CVR) or 1510 (SVR) Fire Exit: 1530F Mortise x 1520F (CVR) or 1510F (SVR)
<b>Operating Trim</b>	630F, 650F, 660F or 670F Series (Active) x 620F or 630F Series (Dummy or Active)
<b>Ordering Example</b>	1 each: 1530-L8F x AU356F x RHR x 605, plus 1 each 1510F x AU629F x LHR x 605

### One Rim - One Vertical Rod Exit Device


- An economic solution for light traffic openings
- Flush or wide stile metal, wood or composite doors

<b>Exit Device</b>	Panic Exit: 1500 Rim x 1510 SVR
<b>Operating Trim</b>	620F or 630F Series
<b>Ordering Example</b>	1 each: 1500-48" x RHR x 632F x 793 x 1510-48" x LHR x 634F x 626

## CYLINDERS

## Rim

The following chart details rim cylinders for use with 620F and 630F trims:



Collar Requirements*					
Model #	Description	Pins	Length	620F	630F
1109	Standard Fixed Core	6	1-1/4"	No Collar	No Collar
1109	Standard Fixed Core	7	1-7/16"		KP4
1709	CMK	6	1-15/16"	1765.250	1765.250
1709	CMK	7	1-5/8"		1765.406
1193	LFIC Complete	6	1-7/16"	1765.344	1765.250
1193	LFIC Complete	7	1-5/8"		1765.406
5109	Security Fixed Core	6	1-9/16"	1765.250	
5109	Security Fixed Core	7	1-7/16"		
U5109	High Security Fixed Core	6	1"	No Collar	No Collar
U5109	High Security Fixed Core	7	1"		
5193	Security LFIC Complete	6	1-7/16"	1765.250	1765.250
5193	Security LFIC Complete	7	1-5/8"	1765.344	1765.406
K300	ACCENTRA KeyMark® Standard Fixed Core	6	1-1/8"	KP4	1765.250
K300	ACCENTRA KeyMark Standard Fixed Core	7			
K840/ K880	ACCENTRA KeyMark LFIC Complete / Housing Only	6	1-7/16"	1765.406	1765.500
K840/ K880	ACCENTRA KeyMark LFIC Complete / Housing Only	7	1-5/8"	1765.563	1765.719
K640/ K680	ACCENTRA KeyMark SFIC Complete / Housing Only	6	1-1/4"	KP4	1765.250
K640/ K680	ACCENTRA KeyMark SFIC Complete / Housing Only	6 or 7	1-3/8"	1765.187	1765.406
A640/ K680	Best® Keyway SFIC Complete / Housing Only	6	1-1/4"	KP4	1765.250
A640/ K680	Best® Keyway SFIC Complete / Housing Only	6 or 7	1-3/8"	1765.187	1765.406
2109	Schlage® "C" Keyway Fixed Core. Available 0-bitted or keyed random.	6	1-1/8"	No Collar	No Collar

\*Based on 1-3/4" door thickness. Collar length required must be specified for cylinders and/or housings ordered separately.


LFIC = Large Format Interchangeable Core

SFIC = Small Format Interchangeable Core

## CYLINDERS

### Mortise

The following chart details mortise cylinders for use with 350F/650F, 660F/670F, and KRM200 and KRM200SM mullions:

				350F/650F		660F/670F		KRM 200			
Model #	Description	Pins	Length	Cam	Collar	Cam	Collar	Length	Cam	Collar	
2153	Standard Fixed Core	6	1-1/2"	2160	No Collar	2160	KP4	1-1/8"	2160	1765.312	
2153	Standard Fixed Core	7	1-1/2"					1-1/4"		1765.500	
2196	LFIC Complete	6	1-1/2"					1-1/2"		1765.750	
2197	LFIC Complete	7	1-11/16"		KP4		1765.250	1-11/16"		1765.844	
5153	Security Fixed Core	6	1-1/2"					1-1/8"	2160	1765.312	
5153	Security Fixed Core	7	1-1/2"		No Collar		KP4	1-1/4"		1765.500	
U5153	High Security Fixed Core	6	1-1/8"					NA		NA	
U5153	High Security Fixed Core	7	1-1/4"					NA		NA	
5196	Security LFIC Complete	6	1-1/2"		No Collar		KP4	1-1/2"		1765.750	
5197	Security LFIC Complete	7	1-11/16"					1765.250		1765.844	
K100	ACCENTRA KeyMark® Standard Fixed Core	6 or 7	1-1/2"	KC1	No Collar	KC1	KP4	1-1/8"	KC1	1765.312	
K100	ACCENTRA KeyMark Standard Fixed Core	6 or 7	1-3/4"	Riveted	KP4	Riveted	1765.375	....	....	....	
K820/ K860	ACCENTRA KeyMark LFIC Complete / Housing Only	6	1-1/2"	KC1	No Collar	KC1	KP4	1-1/2"	KC1	1765.750	
K820/ K860	ACCENTRA KeyMark LFIC Complete / Housing Only	7	1-11/16"		KP4		1765.375	1-11/16"		1765.000	
K620/ K660	ACCENTRA KeyMark SFIC Complete / Housing Only	6	1-1/4"		NA		NA	1-1/4"		1765.500	
K620/ K660	ACCENTRA KeyMark SFIC Complete / Housing Only	6 or 7	1-3/8"				No Collar	1-3/8"		1765.563	
K620/ K660	ACCENTRA KeyMark SFIC Complete / Housing Only	6	1-3/4"	Riveted	KP4	Riveted	1765.375	....	....	....	
A620/ K660	Best® Keyway SFIC Complete / Housing Only	6	1-1/4"	KC1	NA	KC1	NA	1-1/4"	KC1	1765.500	
A620/ K660	Best® Keyway SFIC Complete / Housing Only	6 or 7	1-3/8"				No Collar	1-3/8"		1765.563	
A620/ K660	Best® Keyway SFIC Complete / Housing Only	6	1-3/4"	Riveted	KP4	Riveted	1765.375	....	....	....	
2553	Schlage® "C" Keyway Fixed Core. Available 0-bitted or keyed random.	6	1-1/8"	2160	NA	2160	NA	1-1/8"	2160	1765.312	

**Based on 1-3/4" door thickness. Collar length required must be specified for cylinders and/or housings ordered separately.**


**LFIC** = Large Format Interchangeable Core

**SFIC** = Small Format Interchangeable Core

## CYLINDERS

### Cylinder Collars


If required, cylinder collar size must be specified.



#### 1765 Recessed Cylinder Collar

**"A" Dimension:** Thicknesses from 1/16" (2mm) to 1-15/32" (37mm) as required.


**Material:** Brass, Bronze




#### KP4 Flush Mount Cylinder Collar

**Material:** Brass, Bronze

### Cams



2160



KC1

## STRIKES

## Rim Devices

<b>799</b> Standard strike for 1500(F) devices. Supplied with three shims, #12-24 machine screws, and #12 wood screws.	<b>793</b> Optional strike for double door applications without a mullion. Supplied with #10-24 x 3/4" machine screws, two shims (each 1/16" thick), and one locking plate. Panic only.

## Vertical Rod Devices - Top Strikes

<b>791</b> Standard top strike for 1510(F), 1520(F) series devices. Supplied with #10-24 x 3/4" machine screws, two shims (each 1/16" thick), and one locking plate.	<b>797</b> Optional bracket for mounting 791 top strike in flush transom opening. Supplied with 1/4-20 machine screws; SN-134 sex nuts, optional.

## Vertical Rod Devices - Bottom Strikes

<b>790</b> Standard bottom strike for 1510(F), 1520(F) series devices. Press in place.	<b>794</b> Optional bottom strike for fire openings using saddle thresholds or for flush floor mount. Must use for fire openings with 1/2" thresholds. Supplied with #10-24 x 1/2" machine screws and floor anchors.	<b>702</b> Optional bottom strike for bottom pullman latch option. Supplied with #8 x 8/32" combination screws.

## Mortise Devices

	 For (2) #12-24 Screws		
<b>798</b> Standard curved lip ANSI strike used with 1530(F) devices. (1-1/4" lip)	<b>712</b> Optional flat lip ANSI strike used with 1530 devices for pairs of doors with astragals. (7/8" lip)	<b>718</b> Optional open back strike. Permits opening of the inactive door for pairs of doors where approved by door manufacturer.	<b>702</b> Optional strike box for ANSI strikes. 7/8" (22mm) deep.

## ACCESSORIES


### Specialty Fasteners

SNB, 3/8" (10mm) diameter sex nuts for screws packed with exit devices. Supplied in exact number required on factory orders, or use packs as follows. Specify finish.

SN134 - Pack of (4) 1/4-20 sex nuts.

Torx® Security Screws - to deter tampering, supplied only with product order.

### Bottom Pullman Latch



(P/No. 60-7010-0051-999), for use only with 1510 SVR devices in openings with pullman latch threshold as shown, threshold by others, or 702 floor strike.

To order with devices, specify "BPL."

### Extension Rods

Model #	Length
7010-2	2" (51mm)
7010-6	6" (152mm)
7010-12	12" (305mm)
7010-24	24" (610mm)

Specify finish

## MULLIONS


### M200(F) Removable Mullion

M200(F) steel mullions are for use with 1500(F) series exit devices. Mullions may be field cut to fit opening. Gray paint finish.

- M200 panic rated. Tubular steel, 2" x 3" (51mm x 76mm). Specify 7'2".
- M200F 3 hour fire rated. Tubular steel, 2" x 3" (51mm x 76mm). Specify 7'2" or 10'1" (Fire rated up to 8')


**Notes:**

1. For 8' length Mullion must be order as M200F option and cut in the field to 8' size.




### M200(F) Options

**M203 Spacer Block** Recommended for double rabbeted frames where the stop face width is less than the mounting hole spacing or for applications with 5-3/4" (146mm) or less door frames.



**M204 Angle Bracket** Recommended for any header configuration with less than 3" (76mm) of mounting surface.



## MULLIONS

### KRM200(F) Keyed Removable Mullion (KRM)

Keyed removable mullions are for use with 1500(F) series exit devices. They are designed for simple removing when an unobstructed large opening is required and easy replacement and locking to maintain the integrity of the opening.

- KRM200 panic rated. Specify 7'2".
- KRM200F 1-1/2 hour fire rated. Specify 7'2" or 10'1 (Fire rated up to 8')

**Notes:**

1. For 8' length Mullion must be order as KRM200F option and cut in the field to 8' size.

### Split Mullion


- Hassle-free transportation with a 30% smaller packaging size. Mullions may be field cut to fit opening. Gray painted finish. Available only in 8'. When ordering add suffix SM, example M200SM and KRM200SM

#### M200SM Standard

- Panic rated. Specify 8'
- Tubular steel, 2" x 3" (51mm x 76mm).

#### KRM200SM Key Removable Split Mullion

- Easy cylinder installation.
- Panic rated. Specify 8'
- Tubular steel, 2" x 3" (51mm x 76mm).




M200SM      KRM200SM

### KRM Options


#### M203 Spacer Block

Recommended for double rabbeted frames where the stop face width is less than the mounting hole spacing or for applications with 5-3/4" (146mm) or less door frames.




#### M204 Angle Bracket

Recommended for any header configuration with less than 3" (76mm) of mounting surface.



### KRM Features

- Easy cylinder installation.
- Mullion automatically relocks when reinstalled without the use of the cylinder key.
- When ordering, add KR prefix to mullion, example: KRM200 and KRM200F.



### KRM Cylinders

As with any exit device trim, you must order a cylinder and collar if one is required. The keyed removable mullion accepts a mortise cylinder. Refer to page 19 for details.

## TECHNICAL SPECIFICATIONS & LISTINGS

### ANSI/BHMA

Certified ANSI/BHMA A156.3, Grade 1. 

### Fire Listings

1500F series exit devices are UL-cUL Listed for use on fire doors having a rating up to and including 3-hours unless otherwise noted.

Note: Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and ASSA ABLOY ACCENTRA™ makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

### ISO 9001

Designed and manufactured under a certified ISO 9001 quality system.

### Warranty

The 1500 series exit devices carry a one-year warranty. Trims carry a five-year warranty.

The ASSA ABLOY Group is the global leader in access solutions.  
Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions in homes, businesses and institutions. Our offering includes doors, frames, door and window hardware, mechanical and smart locks, access control and service.

**ACCENTRA**

**ASSA ABLOY**

#### **TECHNICAL SUPPORT**

(troubleshooting, product use and application, returns)  
Tel: 855-557-5078  
Email: [techsupport.accentra@assaabloy.com](mailto:techsupport.accentra@assaabloy.com)

#### **CUSTOMER SUPPORT**

(orders, product configuration, pricing, lead-time)  
Tel: 855-557-5078 x2  
Email: [Customerservice.Accentra@assaabloy.com](mailto:Customerservice.Accentra@assaabloy.com)

#### **U.S.A.:**

ASSA ABLOY ACCENTRA™  
225 Episcopal Road  
Berlin, CT 06037-4004  
Tel: 1-800-438-1951  
Fax: 1-800-338-0965  
[www.accentra-assaabloy.com](http://www.accentra-assaabloy.com)

#### **Canada:**

ASSA ABLOY Door Security Solutions Canada  
160 Four Valley Drive  
Vaughan, Ontario L4K 4T9  
Tel: 1-800-461-3007  
Fax: 1-800-461-8989  
[assaabloydss.ca](http://assaabloydss.ca)

#### **International:**

ASSA ABLOY Americas International  
Tel: 1-905-821-7775  
Fax: 1-905-821-1429  
[assaabloyai.com](http://assaabloyai.com)