



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

291D

Automatic Flush Bolt Set for Wood Covered Composite Doors

Applications



PRODUCT SPECIFICATIONS

Bolt:

Bolt Backset: 3/4" (19 mm)

Bolt Throw:

3/4" (19 mm)

Box Quantity:

2

Case Quantity:

40

Category:

Flush Bolts & Coordinating Devices

Certifications:

1-1/2 hour fire rating on wood doors up to 4' wide by 9' tall (B, C, D, and E label rating)
Meets ANSI 156.3 Type #25

Faceplate:

2" x 8-1/2" (45 mm x 216 mm)

Fasteners:

Three #10 x 1" SMS, Six #8 x 1" combo screws, Two plastic anchors

Finishes:

US10B, US32, US32D

Flattened Round Bolt Head:

1/2" (13 mm)

Material:

Stainless steel/brass with steel components

Mortise Strike Length:

2-1/4" (57 mm)

Mortise Strike Width:

15/16" (24 mm)

Notes:

Consists of two 291S
Thermal lock automatically locks inactive door under high fire/heat conditions
280X dust proof strike are recommended for use with these sets
Used in pairs at top and bottom of inactive door
Fully automatic - bolts retract when active door is opened; bolts extend when active door is closed
Non-handed
Bolt head rods are adjustable
To only be used with non-beveled doors