



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 5100 Closer x Extra Heavy Duty Stop Arm 5125

## 5100 Closer x 5125 Extra Heavy Duty Stop Arm



### Applications

Grade 1 Heavy Duty Surface Door Closer adjustable sizes 1-6  
Ideal for schools, hospitals, and other high-use environments



### PRODUCT SPECIFICATIONS

#### Arm:

5125 - Extra Heavy Duty Stop Arm

Box Quantity:  
1

Case Quantity:  
4

#### Certifications:

BHMA Certified ANSI A156.4, adjustable sizes 1-6  
ADA compliant ANSI A117.1 Accessibility Code  
UL/cUL Listed for up to 3 hours  
UL10C Positive Pressure Rated  
UL10B Neutral Pressure Rated  
5100 Door Closer EPD

#### Cover:

Full plastic cover - standard  
Plated metal cover - optional

#### Door Thickness:

1-3/4" (44 mm) - standard  
1-3/8" - 2-1/4" (36 mm - 57 mm) thick door - optional

#### Handing:

Non-handed

#### Material:

Forged steel arm

Maximum Door Weight:  
330 lbs.

#### Notes:

To maximize hinge life and assist in achieving ADA compliance, Hager recommends the use of anti-friction or ball bearing hinges with our door closer products.  
The recommended temperatures for prolonged closer use is between -40° F (-42° C) and 150° F (66° C)  
Any certified BHMA/ANSI A156.4 door closer, regardless of manufacturer, that is installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch a door.  
If arms are ordered separately, there will be a significant difference in price than if purchased with a closer as a complete assembly.  
See adders for more information (add the list price of the option to the list price of the closer and take standard discounts).  
Accessories may not be available in all finishes. Please contact Hager for availability and lead time.

#### Springs:

One piece seamless steel spring tube  
Double heat-treated, steel-tempered springs  
Precision-machined, heat-treated steel piston

#### Valves:

Adjustable latching and sweep speed valves  
Adjustable backcheck valve - Standard  
Delayed action valve - Optional  
Staked valves - Standard

Warranty:  
Lifetime warranty