

FS18S/FS18L

Floor stop

- FS18S - 1 1/2", FS18L - 3 1/2"
- Security door stops designed for use in high vandalism areas
- Molded from black flame resistant, resilient material around a heavy-duty stud
- Once grouted in concrete, leaves no exposed fasteners to be tampered with or removed
- Ideal for jail or security cell areas where floor mounted stops are required
- FS18L also ideal for concrete wall applications

Specifications

Material substrate	Made from rubber
--------------------	------------------

Finishes

- Black rubber

Dimensions - FS18S

Height	Diameter	Stud length
1 1/2"	2"	2 1/2"

Dimensions - FS18L

Height	Diameter	Stud length
3 1/2"	2"	2 1/2"



FS18S

FS18L

FS434

Floor stop

- For undercut doors up to 1 1/2"
- Packed with fasteners for light duty masonry and wood applications
- Soft, resilient black rubber

Specifications

Material substrate	Made from wrought steel
--------------------	-------------------------

Dimensions

Overall height	Base size
2 5/8"	1 1/2" W x 2 3/4" L

Finish

BHMA	Description	Substrate	Finish
604	Zinc Plated	Steel	US2C

Available accessories

- Replaceable soft, resilient black rubber



430

Floor door stop

- For undercut doors up to 1 1/2"
- Welded wood screws for wood applications
- White rubber tip

Specifications

Material substrate	Made from cast brass and aluminum
--------------------	-----------------------------------

Dimensions

Overall height	Base size
2 5/8"	1 1/2" W x 2 3/4" L

Finishes - brass

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
609	Blackened Brass	Brass	US5
613	Oil Rubbed Bronze	Brass	US10B
619	Satin Nickel	Brass	US15
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D

Finishes - aluminum

BHMA	Description	Substrate	Finish
666	Bright Brass	Aluminum	A3
-	Blackened Brass	Aluminum	A5
669	Bright Nickel	Aluminum	A14
673	Aluminum Clear Coat	Aluminum	A92

For other colors, consult factory.

Available accessories

- Replaceable white or black rubber tips

