

Don't Compromise on Security

Stop break-ins before they start with SELECT's **NEW** pre-drilled, full-length, continuous Latch Guard.



SELECT's **NEW** full-length Latch Guards form the ultimate defense for doors in high-risk, low-visibility areas. With pre-drilled holes and included fasteners, Latch Guards offer easy, hassle-free installation for locksmiths who are dedicated to protecting their customers. If you're looking for a doorway that's as strong as your reputation, look no further than SELECT's Latch Guards. Available in Outswing (LGO), Extra-wide Outswing (LGOW) and Inswing (LGI).






Email: customerservice@select-hinges.com

Ph: 800-423-1174 | Fax: 800-423-7107 | www.select-hinges.com

© 2025 SELECT Products Limited Printed in U.S.A. #FL-032025



**SELECT
HINGES™**

OUTSWING

EXTRA-WIDE OUTSWING

INSWING


MATERIAL: Extruded 6063 T6 aluminum alloy.

LENGTHS: 83" and 95" lengths standard for nominal door heights.

FINISHES: All Latch Guards are stocked in Clear, Dark Bronze and Black anodized aluminum.

ORDER: Specify outswing latch guard (LGO), extra-wide outswing latch guard (LGOW) or inswing latch guard (LGI), length and finish. 12-24 x 3/4" self-drilling, thread-forming 410SS Phillips panhead screws, 1/4-20 through-bolts and 1/4-20 shoulder screws (for doors up to 1-3/4" thick) are provided as a standard pack unless otherwise specified. Long barrel nuts available for 2" – 2-1/4" doors. Security shoulder screws optional at extra cost.

LATCH GUARD SCREW COUNT

HINGE LENGTH	DOOR SCREWS	FRAME SCREWS
83"	9	9
95"	9	9