

N-GLS9800 & N-FGLS9800 Series

GRADE 1 Rim Type Narrow Stile Exit Device




***Americans with Disability Act (ADA) compliant**
5 lbs opening force


***Refer to the Price List for Stock Sizes and Finishes**

Specifications

For Doors	Wood, Metal or Aluminum Glass doors with 1 3/4" minimum stile width, 1 3/4" thickness for single or double door application
Chassis	Steel Material
Chassis Cover	Zinc Material
Mounting	Furnished standard with wood and machine screws. Thru-bolts available upon request.
End Cap	Stainless Steel Material
Alarm	Not available
Hand	Non-Handed
Latch Bolt	Stainless Steel, 3/4" throw
Spring	Steel Material
ANSI Standard	A156.3, Grade 1
Rail Assembly	Stainless Steel Material
Strike	246 (Copper), Optional 247 Strike (Copper)
Dogging Feature	Allen-type key furnished standard. Optional Cylinder Dogging Kit not available.
Mullion	Available
UL and ULC Listed	N-GLS9800 Series for Panic & Safety, N-FGLS9800 Series for Fire Exit hardware for all types of 4' x 8' single doors and 8' x 10' double doors for up to 3 hour fire labeled installations. Conforms to ANSI/UL 10C, ANSI/UL 305 standards.
Electronic Functions	ELR (Electrified Latch Retraction) available for both 36" and 48" push bar.
Anti-Microbial Coating	Available on US32D only. Use part # ANTB-EXIT



246 STRIKE



247 STRIKE (OPTIONAL)

DIMENSIONS

Push rail height to finished floor	41" (1041 mm) at center
Push rail projection	
Neutral	2 1/2" (64 mm)
Depressed	1 3/4" (45 mm)
Center case	8" x 3" x 2 3/8" (203 mm x 76 mm x 60 mm)

MODEL	ACTUAL SIZE	MAXIMUM CUT DOWN	DOOR SIZE
N-GLS9800EO36, N-FGLS9800EO36	35"	9"	27" to 36" door width
N-GLS9800EO48, N-FGLS9800EO48	47"	15"	33" to 48" door width

NOTES:

- N-GLS9800 & N-FGLS9800 Exit Devices are intended for use with Narrow Stile applications
- If used for Regular Door/Frames, must cut down device to size, and follow installation for regular door/frame applications.