



DL2 Series

Grade-2 deadbolts



Specifications

Chassis	Steel, zinc dichromated for corrosion resistance
Trim	Free spinning cylinder collar resists wrenching and prying
Handing	Non-handed, completely reversible
Backset	2-3/4" standard, 2-3/8" optional
Latchbolt	Solid brass with 1" throw and anti-saw hardened steel pin insert
Strike	1-1/8" x 2-3/4" square corner
Cylinder Options	6-pin conventional, C keyway, keyed different
Fasteners	Combination screws for wood or metal doors & frames
Door Prep	ANSI A115.2 - 2 1/8" crossbore
Door Thickness	1-3/4" thick
Finishes	US26D/626 satin chrome, US10BE/613e dark oxidized satin bronze, equivalent, US4/606 satin brass, US19/622 matte black

Code compliance

ANSI/BHMA	Meets & exceeds ANSI/BHMA A156.2, Series 4000, Grade 2 standards
UL/cUL	UL listed for "A" label 3 hour fire-rated doors
ADA	2" ADA thumbturn meets ADA & ANSI A117.1 accessibility codes



DL2 Series

Non-keyed functions



DL2-BPT
ANSI E01112

Blank Plate x Inside Thumbturn

Deadbolt thrown or retracted by thumbturn only. Outside blank plate. Bolt automatically deadlocks when fully thrown.



DL2-IND
ANSI -

Occupancy Indicator x Thumbturn

Deadbolt thrown or retracted by thumbturn inside. Outside indicator displays Red "In use" or Green "Vacant". Bolt automatically deadlocks when thrown.

Keyed functions



DL2
ANSI E21522

Single Cylinder x Inside Thumbturn

Deadbolt thrown or retracted by key from outside or by inside thumbturn. Bolt automatically deadlocks when thrown.



Inside thumbturn

Finishes



US26D/626
Satin chrome



US10BE/613e
Dark oxidized satin bronze,
equivalent



*US4/606
Satin brass



US19/622
Matte black

*Satin brass only available in DL2-IND model