

# ELECTRICAL POWER TRANSFER

## Part No. PT1000, PT1000SC

PT200, PT200EZ, PT1000EZ, PT1200EZ, PTC5E, PTC6PLUS (Not Shown)




PT1000

PT1000SC  
Swing Clear Spring Conduit  
Wire Housing



EZ Connect  
Molex Connectors



PT1200 EZ Connect for  
dormakaba

PT200	(2) 18 AWG Wires Max. Rating: 24VDC, 5A or 120VAC NEC, Class 3
PT200EZ	(2) 18 AWG Wires Max. Rating: 24 VDC, 5A or 120 VAC NEC, Class 3
PT1000	(10) 24 AWG Wires Max. Rating: 24VDC, 1A
PT1000EZ	(12) 24 AWG Wires Max. Rating: 24VDC, 1A
PT1200EZ	(10) 24 AWG Wires-Max. RATING 24VDC, 1A (2) 18 AWG Wires-Max. Rating 24VDC, 5A or 120VAC NEC CLASS 3
PTC5E	CAT-5E Standard Ethernet Cable, (Max. 350 MHz), (1) 22 AWG Wire; Max. Rating: 24VDC, 1A
PTC6PLUS	CAT 6 Standard Ethernet Cable, (Max. 550 MHz), (1) 22 AWG Wire; Max. Rating: 24VDC, 1A

### FEATURES

PT1000, PT200, PT1200, PT1200EZ, PTC5E and PTC6PLUS provide the means of transferring electrical power or data from the frame to the door in a secure and discreet manner.

- ▲ PT1200EZ are supplied standard with EZ Connectors
- ▲ PTC5E and PTC6PLUS are supplied with Ethernet cable.
- ▲ Unit mortises into the edges of the door and frame and is completely concealed when the door is in the closed position.
- ▲ All metal construction including back boxes-  
**No plastic parts.**
- ▲ Ideal for high abuse or heavy traffic situations.
- ▲ UL/ULC Listed for use on fire doors.

### STANDARD FINISHES

- ▲ US28 - Brushed Aluminum
- ▲ S5 - Powder Coated Dark Bronze to match US10B Finish

### STANDARD APPLICATIONS

- ▲ 1 3/4" Door thickness
- ▲ Cam lift hinges (up to 1/2" lift) - allowing for 180° door swing
- ▲ Butt hinges up to 5" - allowing for 180° door swing
- ▲ Invisible hinges allowing for 90° door swing
- ▲ Swing Clear Hinges with "SC" option
- ▲ 5 1/2" butt hinges - allowing for 130° door swing
- ▲ 6" butt hinges - allowing for 110° door swing
- ▲ Up to 3/4" offset pivots - allowing for 180° door swing
- ▲ Not for use with pocket pivots, butt hinges larger than 6", 1 1/2", 1/2" offset pivots or center hung doors.
- ▲ Approximate shipping weight: 3 lbs.
- ▲ Patent Pending

### OPTIONS

- ▲ SEC - Security Fasteners
- ▲ EZ - PT1000 & PT200 available with Molex® plug-in connectors option
- ▲ SC - Swing Clear option available for PT1000 & PT200



abhmfg.com

**Made in ITASCA, USA & Family-Owned**  
**Our parts are made of MORE.**

**Architectural Builders Hardware Manufacturing Inc.**

740 Hilltop Drive, Itasca, IL 60143  
TEL 630.875.9900 FAX 800.932.9224

**Don't be shy. If you have any ?s call on us.**