

MEETS
The Buy American Act

Meets ADA requirements
Specially designed for
Barrier Free Application
Exceeds BHMA/ANSI A156.2
Series 4000, Grade 1 requirements
Exceeds 1,000,000 cycles


CALYPSO

CLUTCH MECHANISM

FIXED THRU BOLT INSTALLATION

UL US
3 HOUR FIRE RATED
UL10C, UBC7-2-1997

Lifetime
Warranty



MHM DESIGN



SAN DESIGN

SPECIFICATIONS

APPLICATIONS

For offices, schools, hospitals, apartments, hotel/motel, residential, commercial and public buildings.

DOOR RANGES

1 3/8" to 2" thickness doors.

BACKSET

2 3/4" Standard, 2 3/8", 3 3/4", 5" and 2 3/4" anti-friction latch with 3/4" throw for pair of fire doors optional.

LATCHBOLT

1/2" Throw solid brass, reversible for RH or LH applications. UL Listed.

LATCH FACEPLATE

2 1/4" x 1 1/8", adjustable for flat or beveled doors 1/8" in 2", for 2 3/4" backset.
Optional 2 1/4" x 1 1/8" for 2 3/8" backset.

STRIKES

ASA strike standard, "T" and full lip strike available on request.

EXPOSED TRIM

Wrought brass, bronze or stainless steel, levers are Zinc casting, plated to match trim finish.

CYLINDER & KEYWAYS

6 pin solid brass "C" keyway standard. Schlage E, Schlage C-K, Russwin D1-2-3-4, Corbin 59/60, Corbin-Russwin L4, Sargent LA-LB-LC, Falcon/Weiser E, Arrow A, Yale 8, Yale GA and Kwikset. Can also accept Medeco, Assa, Kaba and Cal-Royal (HSK) High Security Cylinders.

INTERCHANGEABLE CORE

Interchangeable Core locks will accept compatible 6 or 7 pin cores with BEST, FALCON and ARROW. Prefix "IC" before part number. Available combined or uncombined. Temporary construction cores available. Factory keying with control key and master key available.

ANSI STANDARDS

Meets or exceeds requirements of BHMA/ANSI A156.2 Series 4000, Grade 1

TACTILE & LEAD LINING available upon request.

CALYPSO CAL SERIES FINISHES AND FUNCTIONS




FINISHES AVAILABLE


BHMA SYMBOL	US CODE	DESCRIPTION
605	US3	Polished Brass
606	US4	Satin Brass
609	US5	Antique Brass
612	US10	Satin Bronze
613	US10B	Oil Rubbed Bronze
619	US15	Satin Nickel
625	US26	Polished Chrome
626	US26D	Satin Chrome

Refer to price list for stock finishes and functions


DOOR PREPARATION



**Lifetime
Warranty**




CAL00
ICCAL00
ANSI: F109
FED#161A



ENTRANCE/OFFICE LOCK

Turn/Push button locking. Pushing and turning button locks outside lever requiring use of key until button is manually unlocked. Pushing button locks outside lever until unlocked with key or inside lever is turned.


CAL07
ICCAL07
ANSI: F110



CLASSROOM INTRUDER

Latch bolt is operated by rotating the inside lever, or rotating the outside lever only when not locked from the inside or outside key. Outside lever is locked and unlocked by turning the key inside or outside lever. Inside lever cannot be locked.


CAL02
ICCAL02
ANSI: F91
FED#161G



STORELOCK

Dead locking latch bolt operated by lever from either side, except when both levers are locked by key in lever from either side.


CAL09
ICCAL09
ANSI: F87
FED#161W



INSTITUTION

Dead locking latch bolt operated by key in lever from either side. Both lever always fixed.


CAL03
ICCAL03
ANSI: F84
FED#161R



CLASSROOM

Dead locking latch bolt operated by lever from either side except when outside lever is locked from outside by key. When outside lever is locked, latch bolt is operated by turning inside lever.


CAL101
ICCAL101
ANSI: F90
FED#161T



DORMITORY

Dead locking latch bolt operated by lever from either side except when outside lever is locked by key or by push button on inside lever. Key in outside lever locks or unlocks outside lever. Outside key releases push button when locked from inside. Rotating inside lever or closing the door releases push button.


CAL04
ICCAL04
ANSI: F80
FED#161S



COMMUNICATING

Dead locking latch bolt operated by lever from either side. Turning key in either lever locks or unlocks its own lever independently.


CAL20
ANSI: F76
FED#161L



PRIVACY LOCK

Latch bolt operated by lever from either side. Outside lever is locked by push button inside and unlocked by emergency release outside. Turning inside lever or closing door releases push button.


CAL05
ICCAL05
ANSI: F86
FED#161D



STOREROOM

Dead locking latch bolt operated by key in outside lever or by rotating inside lever. Outside lever is always fixed.


CAL30
ANSI: F75
FED#161N



PASSAGE SET

Latch bolt operated by lever from either side at all times.

CAL06
ICCAL06
ANSI: F88
FED#161C



VESTIBULE

Dead locking latch bolt operated by lever from either side except when outside lever is locked by key from inside. Latch bolt may be retracted by key in outside lever or by rotating inside lever.

CAL40



DUMMY LEVER

Single dummy trim for one side of door. Pull only.

“IC” Indicates function available with BEST, FALCON & ARROW Interchangeable Core.

HOW TO ORDER: For “SPA” or “MHM” designs, replace design name. Example: CAL00 entrance in “SAN” is SAN00.

OTHER FUNCTIONS NOT LISTED AVAILABLE UPON REQUEST